


C0.5 | C0.7

ENGINES



C0.5

Specifications

	C0.5	C0.7 U.S. EPA Tier 4 Final
Engine Configuration ...	In-Line 2, Diesel	In-Line 3, Diesel
Bore x Stroke	67 x 72 mm (2.6 x 2.8 in)	67 x 72 mm (2.6 x 2.8 in)
Displacement	0.5 liters (31.0 in ³)	0.76 liters (46.4 in ³)
Ship Weight	57 kg (126 lbs)	71 kg (156.5 lbs)
Approximate Dimensions:		
Length	407 mm (16.0 in)	480 mm (18.9 in)
Width	371 mm (14.6 in)	371 mm (14.6 in)
Height	523 mm (20.6 in)	528 mm (20.8 in)

C0.5 Ratings

	C Rating (Intermittent)		
	bkW	bhp	rpm
NA			
	8.2	11.0	2800
	8.8	11.8	3000
	10.2	13.7	3600

Available for Europe and, depending on applicable emission standards, may be introduced in other regulated areas.

C0.7 Ratings

	C Rating (Intermittent)		
	bkW	bhp	rpm
NA			
	12.2	16.4	2800
	13.2	17.7	3000
	15.3	20.5	3600

Available for Europe and, depending on applicable emission standards, may be introduced in other regulated areas.

C0.7 U.S. EPA Tier 4 Final Ratings

	C Rating (Intermittent)		
	bkW	bhp	rpm
NA			
	8.8	11.8	2200

U.S. EPA Tier 4 Final Nonroad emission standards. Nonroad engines less than 19 bkW (25 bhp) are not currently subject to EU emission standards.