


C13 ACERT

ENGINE



Specifications

China Stage III Nonroad, U.S. EPA Tier 3 Equivalent or U.S. EPA Tier 2 Equivalent, EU Stage IIIA Equivalent or EU Stage II Equivalent

Engine Configuration . . .	In-Line 6, Diesel
Bore x Stroke	130 x 157 mm (5.1 x 6.2 in)
Displacement	12.5 liters (763 in ³)
Ship Weight	908.4 kg (2002.7 lbs)

Approximate Dimensions:

Length	1295 mm (50.98 in)
Width	1186 mm (46.69 in)
Height	1053.8 mm (41.49 in)

China Stage III Nonroad, U.S. EPA Tier 3 Equivalent, EU Stage IIIA Equivalent Ratings*

A Rating (Continuous)	B Rating			C Rating (Intermittent)			D Rating			E Rating				
	bkW	bhp	rpm	bkW	bhp	rpm	bkW	bhp	rpm	bkW	bhp	rpm		
287	385	1800-2100	310	415	1800-2100	328	440	1800-2100	354	475	1800-2100	388	520	1800-2100

U.S. EPA Tier 2 Equivalent, EU Stage II Equivalent Ratings**

TA (ATAAC)	B Rating			C Rating (Intermittent)		
	bkW	bhp	rpm	bkW	bhp	rpm
	310	415	1800-2100	328	440	1800-2100

*China Stage III Nonroad emission standards. U.S. EPA Tier 3 Nonroad equivalent emission standards (not currently EPA certified). EU Stage IIIA Nonroad equivalent emission standards (non-current for EU). Available for other regulated and non-regulated areas.

**U.S. EPA Tier 2 Nonroad equivalent emission standards (not currently EPA certified). EU Stage II Nonroad equivalent emission standards (non-current for EU). Available for other regulated and non-regulated areas.